



The material: **Material:**

Insulators: Insulator: Glass filled PBT UL94V-0, Blue

Contact a: Contacts: Male-Brass, Female-Phosphor Bronze

Electric plating: Plating: Contact Gold plating over Nickel

Electrical properties: **Electrical Characteristics:**

Contact resistance: Contact Resistance: 30mmax. at DC 100mA

Insulation resistance: Insulator Resistance: 1000Mmin. at 500V DC

Pressure: Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute

Working current: Current Rating: 2 AMP

Operating temperature range: Operating Temperature: -55°C~+105°C

Cable specifications: Cable: 1.27mm (0.050") pitch flat cable

\*Standard Gold Flash

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2



深圳市强泰盛电子有限公司  
Shenzhen Qiangtaisheng Electronic Co. LTD.  
TEL:86-755-82599792 FAX:86-755-27313473

SCALE: AS SHOWN	UNIT: mm
DRAWN WAN	06/17/13
CHECKED CHEN	06/17/13
APPROVED CHEN	06/17/13

DRAWN NAME:	Pressure row internal buckle
	9 public riveting
PRODUCT NO.	
FILE NAME:	

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13

SIZE	A4	REV.	A
------	----	------	---