

texture of material: **Material:**
 insulator: Insulator: Glass filled PBT UL94V-0 , Blue
 Contact: Contacts: Male-Brass, Female-Phosphor Bronze
 Electroplated coating: Plating: Contact Gold plating over Nickel
 Electrical performance: **Electrical Characteristics:**
 Contact resistance: Contact Resistance: 30mmax. at DC 100mA
 Insulation resistance: Insulator Resistance: 1000Mmin. at 500V DC
 Withstand voltage: Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute
 Operating current: Current Rating: 2 AMP
 Operating temperature range: Operating Temperature: -55°C~+105°C
 Cable specification: Cable: 1.27mm (0.050") pitch flat cable
 *Standard Gold Flash


UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
.0	±0.5
.0	±0.3
.00	±0.2

QIANGTS 深圳市强泰盛电子有限公司
 Shenzhen Qiangtaisheng Electronic Co. LTD.
 TEL:86-755-82599792 FAX:86-755-27313473

SCALE: AS SHOWN	UNIT: mm
DRAWN WAN	06/17/13
CHECKED CHEN	06/17/13
APPROVED CHEN	06/17/13

DRAWN NAME: Press fit inner buckle
 15 male riveting
 PRODUCT NO.
 FILE NAME:

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13



SIZE A4 REV. A

FILE NAME: