

Instructions:

1. Features:

Insulation impedance :3000MΩ MIN.
 at 500V DC
 Resistance to voltage value :250V AC
 RMS for 1Minute
 Temperature range : -45℃~+85℃

2. Material:

Rubber core : PBT rated (black)
 The shell : ferroalloy/Copper alloy/
 Stainless steel front shell with nickel
 plating and rear shell with tin plating/
 passivation

210A 15 M 1 X
 1 2 3 4 5

1. Series number:

210A=DC end type light hole

2. PIN a distinction between:

09=9PIN 15=15PIN 25=25PIN
 37=37PIN 50=50PIN

3. Male female to distinguish:


F=The mother M=The male

4. Classification of Plastics:

1=vinyl

5. The shell to distinguish:

A=Iron shell 12H B=Iron shell 24H
 C=Iron shell 48H D=Copper shell
 E=Passivation of stainless steel
 F=Stainless steel nickel plating
 G=Iron shell plating

UNLESS OTHERWISE SPECIFIED TOLERANCE		深圳市强泰盛电子有限公司	
ANG.	±5°	Shenzhen Qiangtaisheng Electronic Co. LTD.	
0.	±0.5	TEL:86-755-8259792 FAX:86-755-27313473	
.0	±0.3		
.00	±0.2		
SCALE: AS SHOWN	UNIT: mm	DRAWN NAME: DC15 male end light hole	
DRAWN WAN	07/07/08	PRODUCT NO. 210A15M1X	
CHECKED CHEN	07/07/08	FILE NAME: 210A15M1X	
APPROVED CHEN	07/07/08	DATE 06/17/13	
SIZE A4	REV. A		

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13