



Explain:

- Characteristic:
 - Rated voltage :500V AC MIN
 - Rated current :5A
 - Contact impedance :30mΩ MAX.
 - Insulation impedance :3000MΩ MIN. at 500V DC
 - Withstand voltage value :500V AC RMS for 1Minute
 - Scope of work : -55℃~+105℃
 - Shell salt spray : Above 48H
- Material Science:
 - Rubber core : PBT rated
 - Car PIN : copper alloy
 - Housing : ferroalloy/copper alloy/Stainless steel front shell nickel plating and rear shell tin plating/passivation

202A 25 F X X XX C X
 1 2 3 4 5 6 7 8

- Serial number:
202A=DB head turning needle optical hole
- PIN distinguishing:
09=9PIN 15=15PIN 25=25PIN
37=37PIN 50=50PIN
- Male female distinction:
F=mother M=male
- Plastic division:
1=PBT White glue 2=PBT Black glue
- Terminal material differentiation:
H=brass P=Phosphor copper
- Terminal electroplating μ Numerical differentiation:
01=1u gold AA=1.5u gold 02=2u gold.....
- Specification differentiation of gold terminal:
C=routine
- General enclosure differentiation:
1=Iron shell 2=Copper shell
3=Stainless steel passivation
4=Stainless steel nickel plating

UNLESS OTHERWISE SPECIFIED TOLERANCE		深圳市强泰盛电子有限公司 Shenzhen Qiangtaisheng Electronic Co. LTD. TEL:86-755-8259792 FAX:86-755-27313473	
ANG.	±5°		
0.	±0.5		
.0	±0.3		
.00	±0.2		
SCALE: AS SHOWN	UNIT: mm	DRAWN NAME: DB25 bus needle polished hole	
DRAWN WAN	06/17/13	PRODUCT NO. 202A25FXXXXCX	
CHECKED CHEN	06/17/13	FILE NAME: 202A25FXXXXCX	
APPROVED CHEN	06/17/13		
REV. A	DESCRIPTION	DATE	SIZE A4 REV. A

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13