



Explain:

1. characteristic:

Insulation impedance :3000MΩMIN. at 500V DC  
 Withstand voltage value :250V AC RMS for 1Minute  
 Temperature range : -45°C+85°C

2. Material Science:

Rubber core : PBT rated (black)  
 Iron shell : SPCC, Front shell  
 nickel plating Rear shell tin plating

110A 15 F 1 X  
 1 2 3 4 5

1. Serial number:

110A=HDEC Punching end type smooth hole

2. PIN distinguishing:

15=15PIN 26=26PIN 44=44PIN  
 62=62PIN 78=78PIN

3. Male female distinction:

F=mother M=male

4. Classification of plastics:

1=Black glue

5. Iron shell division:

A=Iron shell 12H B=Iron shell 24H  
 C=Iron shell 48H  
 D=Copper shell E=Stainless steel passivation  
 F=Stainless steel nickel plating  
 G=Gold plated iron shell

UNLESS OTHERWISE SPECIFIED TOLERANCE		深圳市强泰盛电子有限公司	
ANG.	±5°	Shenzhen Qiangtaisheng Electronic Co. LTD.	
0.	±0.5	TEL:86-755-8259792 FAX:86-755-27313473	
.0	±0.3		
.00	±0.2		
SCALE: AS SHOWN	UNIT: mm		
DRAWN WAN	07/07/08	DRAWN NAME: HDEC15 female tapping end type optical hole	
CHECKED CHEN	07/07/08		
APPROVED CHEN	07/07/08	PRODUCT NO. 110A15F1X	
REV. A	06/17/13	FILE NAME: 110A15F1X	

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13