

Explain:

1.Characteristic:

- Rated voltage :500V AC MIN
- Rated current :5A
- Contact impedance :30mΩ MAX.
- Insulation impedance :3000MΩ MIN. at 500V DC
- Withstand voltage value :500V AC RMS for 1minute
- Scope of work : -55℃~+105℃
- Shell salt spray : Above 48H

2.Material Science:

- Rubber core : PBT rated
- Car PIN : copper alloy
- Housing : ferroalloy/copper alloy/Stainless steel front shell nickel plating and rear shell tin plating/passivation

102A 26 F X X XX C X
1 2 3 4 5 6 7 8

1. Serial number:

- 102A=HDB head turning needle optical hole
- 2.HDB head turning needle optical hole:
15=15PIN 26=26PIN 44=44PIN
62=62PIN 78=78PIN

3. Male female distinction:

- F=female M=male

4. Plastic division:

- 1=PBT White glue 2=PBT Black glue

5. Terminal material differentiation:

- H=brass P=Phosphor copper

6. Terminal electroplating μ Numerical differentiation:


- 01=1u gold AA=1.5u gold 02=2u gold....

7. Terminal specification differentiation:

- C=routine

8. Enclosure differentiation:

- 1=Iron shell 2=Copper shell
- 3=Stainless steel passivation
- 4=Stainless steel nickel plating

UNLESS OTHERWISE SPECIFIED TOLERANCE		ANG. ±5°		0. ±0.5		.0 ±0.3		.00 ±0.2		 深圳市强泰盛电子有限公司 Shenzhen Qiangtaisheng Electronic Co. LTD. TEL.:86-755-82599792 FAX:86-755-27313473	
SCALE: AS SHOWN		UNIT: mm		DRAWN WAN		06/17/13		DRAWN NAME: HDB26 bus needle optical hole			
CHECKED CHEN		06/17/13		APPROVED CHEN		06/17/13		PRODUCT NO. 102A26FXXXXCX			
REV. A		DESCRIPTION		DATE		SIZE A4		REV. A		FILE NAME: 102A26FXXXXCX	

A		ECN-20130617001(WAN)		06/17/13		APPROVED CHEN		06/17/13		PRODUCT NO. 102A26FXXXXCX	
REV. A		DESCRIPTION		DATE		SIZE A4		REV. A		FILE NAME: 102A26FXXXXCX	