



Explain:

1. characteristic:  
 Insulation impedance :3000MΩ MIN. at 500V DC  
 Withstand voltage value :250V AC RMS for 1Minute  
 temperature range : -45℃~+85℃
2. Material Science:  
 Rubber core : PBT rated (black)  
 Iron shell : SPCC, Front shell nickel plating Rear shell tin plating

110A 44 M 1 X  
 1 2 3 4 5

1. Serial number:  
 110A=HDEC end punched optical hole
2. PIN distinguishing:  
 15=15PIN 26=26PIN 44=44PIN  
 62=62PIN 78=78PIN
3. Male female distinction:  
 F=female M=male
4. Classification of plastics:  
 1=Black glue
5. Iron shell division:  
 A=Iron shell 12H B= Iron shell 24H  
 C=Iron shell 48H D=Copper shell  
 E=Stainless steel passivation  
 F=Stainless steel nickel plating  
 G=Gold plated iron shell

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2
SCALE: AS SHOWN	UNIT: mm

**QIANGTS** 深圳市强泰盛电子有限公司  
 Shenzhen Qiangtaisheng Electronic Co. LTD.  
 TEL:86-755-82599792 FAX:86-755-27313473

REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME:
A	ECN-20130617001(WAN)	06/17/13	A4	A	110A44M1X
					DRAWN NAME: HDEC44 male end type optical hole
					PRODUCT NO. 110A44M1X