

Specification for waterproof screws

Part number	Xsize	Asize	In the teeth
	4.8	3.2	4#40
	4.8	7	4#40
	5.8	7	4#40

Instructions:

1.Features:


- Rated voltage :500V AC MIN
- Rated current current :5A
- Impedance of contact :30mΩ MAX.
- Resistance of insulation :5000ΩMIN. at 500V DC
- Voltage resistance value :500V AC RMS for 1Minute
- Range of temperature : -55℃-+105℃
- Water resistance class :IP67

2.material:

- Rubber core : PBT Add fine 30%(UL94V-0) (Black white)
- Car PIN : C3604(BRASS), Gold plated 3U "
- The iron shell : SPCC, The front shell is nickel plated and the rear shell is tin plated

3.Precautions:

- a.After 48 hours of salt spray test, no oxidation rust phenomenon
- b.The finished product should not have broken bent needles.

UNLESS OTHERWISE SPECIFIED TOLERANCE		ANG. ±5°		 深圳市强泰盛电子有限公司 Shenzhen Qiangtaisheng Electronic Co. LTD. TEL:86-755-8259792 FAX:86-755-27313473		
0. ±0.5		.0 ±0.3				
.00 ±0.2						
SCALE: AS SHOWN		UNIT: mm				
DRAWN	WAN	06/17/13	DRAWN NAME:	HDB62 female waterproof riveting		
CHECKED	CHEN	06/17/13	PRODUCT NO.			
A	ECN-20130617001(WAN)	06/17/13	APPROVED	CHEN	06/17/13	FILE NAME:
REV.	DESCRIPTION	DATE	SIZE	A4	REV.	A