

Instructions:

1. Features:

Resistance of insulation :3000MΩMIN. at 500V DC  
 Voltage resistance value :250V AC RMS for 1Minute  
 Range of temperature : -45℃+85℃

2. Material:

Rubber core : PBT rated (black)  
 The iron shell : SPCC, The front shell is nickel plated and the rear shell is tin plated

110A 62 F 1 X  
 1 2 3 4 5

1. Serial number:

110A=HDEC end type light hole

2. PIN bit differentiation:

15=15PIN 26=26PIN 44=44PIN  
 62=62PIN 78=78PIN

3. Male female distinction:


F=female M=male

4. Classification of Plastics:

1=vinyl

5. Iron shell distinction:

A=Iron case 12H B=The iron shell 24H  
 C=The iron shell 48H D=Copper shell  
 E=Passivation of stainless steel  
 F=Stainless steel nickel plating  
 G=Gilding of iron case

UNLESS OTHERWISE SPECIFIED TOLERANCE		ANG. ±5°		0. ±0.5		.0 ±0.3		.00 ±0.2		 深圳市强泰盛电子有限公司 Shenzhen Qiangtaisheng Electronic Co. LTD. TEL:86-755-8259792 FAX:86-755-27313473					
SCALE: AS SHOWN				UNIT: mm				DRAWN NAME: HDEC60 female punched end light hole							
DRAWN WAN				07/07/08				CHECKED CHEN				07/07/08			
APPROVED CHEN				07/07/08				DATE 06/17/13				PRODUCT NO. 110A62F1X			
REV. A				SIZE A4				REV. A				FILE NAME: 110A62F1X			

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13